

TECHNICAL SPECIFICATIONS	Display	Touchscreen, color, 1280 ~ 800 TFT 256 mm (10.1 in)
	Interfaces	RJ45 LAN 10/100/1000 Mbit/s
		Two USB 2.0 ports
		One USB 3.0 port
	Storage	Internal 80 GB hard drive minimum with G-shock protection
	Battery	Rechargeable lithium-polymer battery
	Battery Life	12 hours of operation
	Recharge Time	1.5-2 hours
	Power supply	Autoswitching - AC/DC adapter, input AC: 100 – 240 V; 50/60 Hz;
	Computer	Quad-core processor/4 GB RAM/Windows10
GENERAL SPECIFICATIONS	Distance Range settings	5, 20, 50, 125 km
	Size (H x W x D)	199-210 mm x 333-350 mm x 119-125 mm
	Weight	3-5 kg
	Temperature Operation	0 °C to 50 °C
	Temperature Storage	-40 °C to 60 °C
	Relative humidity	≤95 % non-condensing
BUILT-IN POWER METER SPECIFICATIONS	Calibrated wavelengths (nm)	850, 1300, 1310, 1490, 1550, 1625, 1650
	Optional CWDM calibrated wavelengths (nm)	1270, 1290, 1310, 1330, 1350, 1370, 1390, 1410, 1430, 1450, 1470, 1490, 1510, 1530, 1550, 1570, 1590, 1610, 1383, 1625
	Power range (dBm)	27 to -50
	Uncertainty (%)	±5 % ± 10 nW
	Display resolution (dB)	0.01 = max to -40 dBm
	External Printer Capable	Yes
	مدت زمان انجام المتعلم (روز)	10
	مدت زمان تعویب (روز)	45
	مدت زمان آموزش رایگان (روز)	سه نفر روز
	مدت زمان خدمات پس از فروش (سال)	5
Time Table		

[Handwritten signature]

اداره کل
طرح و مهندسی شبکه انتقال
شرکت ارتباطات مخابراتی ایران

- 1- یک عدد باتری یوکی
- 2- کیف محافظ
- 3- کابل پرینتر + کابل نمایشگر